

## **PART 2. Signs**

### **CHAPTER 2A. GENERAL**

#### **Section 2A.06 Design of Signs**

Amended and add the following:

##### **Support:**

North Carolina has many special and/or unique sign designs. The "Sign Design Request" link on NCDOT's Signing Webpage at <http://www.ncdot.org/doh/preconstruct/traffic/congestion/SIGN/> has information regarding how to obtain or create a special sign design.

### **CHAPTER 2C. WARNING SIGNS**

#### **Section 2C.38 Design of Warning Signs**

Amended and add the following:

##### **Standard:**

**A If used, Reduced Speed Limit Ahead (W3-5) sign shall be installed at least 600 feet in advance of the beginning of the speed zone, indicating a change in the speed limit.**

### **CHAPTER 2D. GUIDE SIGNS – CONVENTIONAL ROADS**

#### **Section 2D.11 Design of Route Signs**

Amended and add the following:

##### **Standard:**

**The official route sign for N.C. routes shall be a diamond shield. Three-digit N.C. Route signs shall be at least 24" x 24" in size for ground mounted guide signs.**

**Three digit N.C. Route signs shall be at least 36" x 36" in size for overhead mounted guide signs.**



**M1-5**

**Section 2D.43 Street Name Sign (D3-1)**

Amended and add the following:

**Standard:**

**Street Name signs shall be the sole responsibility of the municipality. These signs shall be erected in such a manner that they will not interfere with other signs, signals, or operation of signals. Street Name signs shall be maintained by those responsible for placing the signs.**